







Typ / Type: ER/EQ 400-4		Art.-No.: E10-40005 / E00-40005	
U	230V (50Hz)	Δp _{fa} min	-- Pa
P ₁	0,21 kW	ΔI	4 %
I _N	0,95 A	I _A / I _N	2.2
n	1340 min ⁻¹		IP54
C _{400V}	5 μF		01.025
t _R	60 °C		7 / 9 kg

Typ / Type: DR/DQ 400-4		Art.-No.: E10-40055 / E00-40055	
U	400V (50Hz)	Δp _{fa} min	-- Pa
P ₁	0,2 kW	ΔI	-- %
I _N	0,42 A	I _A / I _N	3.0
n	1340 min ⁻¹		IP54
C _{400V}	-- μF		01.006
t _R	65 °C		7 / 9 kg

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Gehäuse / casing	53	58	67	67	68	64	55

LWA _{rel} A-bewertet bei V=0,5*V _{max} LWA _{rel} A-weighted at V=0,5*V _{max}	fM [Hz]						
	125	250	500	1K	2K	4K	8K
LWA ₅ [dB(A)] Gehäuse / casing	53	58	67	67	68	64	55

